

## Characteristics Labster ESD standing rest

Article:	9106E integral foam	
Dimensions in mm	Seat:	H 650-850 B 360 T 300
Packing data	Weight:	7,0 kg
	Volume:	0,15 m <sup>3</sup>



Base equipment		Benefit
Hygienic quality	Consistent hygienic design. Quasi seamless, no nooks and crannies, soft cover on ring release. Completely washable and resistant to disinfectants	Cleaning / decontamination is quick, easy, thorough and safe.
Laboratory qualification	GMP-compatible and suitable for use in clean rooms. Can be used in laboratories of safety class S1 to S3.	Suitable for laboratory and hygiene-critical areas of all types and in particular for use in the health sector, biotechnology and pharmaceuticals.
Conductivity	Volume conductive plastic parts Typical discharge resistance of 10 <sup>6</sup> Ω	Exceeds the requirements of ESD protection according to standard DIN EN 61340-5-1 100% ESD protection
Seat design	<b>Integral foam cushion (PU)</b> with seamless upholstery technique. Washable and resistant to disinfectant. Colour black (2000)	The integral foam cushions offer good seating comfort and are resistant to mechanical loads.
Seat height	Infinitely variable seat height adjustment from 650-850 mm through self-supporting safety pneumatic spring	Large seat height adjustment range.
Technology	User friendly ring release for seat height	The height can be adjusted at any handle position around the aid.
Pendulum base	Pendulum base of plastic. The complete upper part of the standing aid tilts by up to 7°.	The pendulum base follows your movement and allows you to reach out on all sides without having to stand up.
Material used	All materials are pure and recyclable.	Environmentally friendly
Standards	DIN EN ISO 14644-1 Air purity class 3 GMP - compatible Laboratory safety class S1 to S3 GS symbol for „Tested safety“ Quality management system DIN EN ISO 9001 EEC Directive No. 1836/93 and Environmental management system DIN EN ISO 14001	Certified laboratory suitability Tested by Fraunhofer Institut IAO Safeguarded procurement.
Warranty	5 year long-term warranty of which 3 year full warranty	Guaranteed quality and high efficiency