



- A. These boxes are made of conductive polypropylene with a surface resistance of  $<10E5$  ohms, conductive as defined in EN 61340-5-1 Edition 1.0 2007-08 clause 5.3.4 Packaging.
- B. The boxes have an integrally hinged lid that clips to the base.
- C. They are supplied in various sizes and can be lined with 6mm thick conductive black insertion foam in the base and 6mm conductive black foam in the lid.
- D. It is recommended that once filled the boxes be taped shut with an ESD warning label.

Item	Description
<a href="#">241060</a>	Rigid Conductive Box, 35 x 35 x 11mm, Empty
<a href="#">241065</a>	Rigid Conductive Box, 35 x 35 x 11mm, 6mm HD in Base Only
<a href="#">241045</a>	Rigid Conductive Box, 75 x 51 x 14mm, Empty
<a href="#">241050</a>	Rigid Conductive Box, 75 x 51 x 14mm, 6mm HD in Base/FX in Lid
<a href="#">241025</a>	Rigid Conductive Box, 90 x 64 x 16mm, Empty
<a href="#">241030</a>	Rigid Conductive Box, 90 x 64 x 16mm, 6mm HD in Base/FX in Lid
<a href="#">241010</a>	Rigid Conductive Box, 108 x 83 x 13mm, Empty
<a href="#">241015</a>	Rigid Conductive Box, 108 x 83 x 13mm, 6mm HD in Base/FX in Lid
<a href="#">241105</a>	Rigid Conductive Box, 138 x 97 x 33mm, Empty
<a href="#">241000</a>	Rigid Conductive Box, 230 x 128 x 20mm, Empty
<a href="#">241005</a>	Rigid Conductive Box, 230 x 128 x 20mm, 6mm HD in Base/FX in Lid
<a href="#">241085</a>	Rigid Conductive Box, 230 x 128 x 30mm, Empty
<a href="#">241090</a>	Rigid Conductive Box, 230 x 128 x 30mm, 6mm HD in Base/FX in Lid
<a href="#">241095</a>	Rigid Conductive Box, 230 x 128 x 40mm, Empty
<a href="#">241100</a>	Rigid Conductive Box, 230 x 128 x 40mm, 6mm HD in Base/FX in Lid

"All generators of electrostatic charges, such as untreated plastic films, foams, synthetic fibres, adhesive tapes, etc., must be prohibited for use as intimate or proximity packaging material and should be kept away from EPA (ESD Protected Area)". (EN 61340-5-2 section 6)



Made in Britain

## Rigid Conductive Boxes

VERMASON  
 UNIT C, 4TH DIMENSION, FOURTH AVENUE, LETCHWORTH,  
 HERTS, SG6 2TD UK  
 PHONE: +44 (0) 1462-672005, FAX: +44 (0) 1462-670440  
 E-MAIL: [Service@Vermason.co.uk](mailto:Service@Vermason.co.uk), INTERNET: [Vermason.co.uk](http://Vermason.co.uk)

Drawing Number  
**241000**

DATE:  
 July 2009