

Product Description

9148 is a polyester film with a pressure-sensitive silicone thermoset adhesive system.

Performance Features

Special adhesives and backing resist fumes and chemicals for low/no residue application. Controlled unwind enables easy manual or machine application and the tough polyester film will not break or tear during application or removal.

Applications

Designed to perform in masking applications requiring high chemical resistance. Also excellent for splicing requiring silicone adhesives.

Technical information

Total Thickness (mm)	0,06
Adhesive Thickness	0,03
Backing Thickness (mm)	0,03
Adhesive System	Silicone
Adhesion to Steel (N/25mm)	8
Tensile Strength (N/25mm)	101
Elongation at Break (%)	100
Temperature	180°C
Colour	Blue transparent

Important: The performance of all adhesive products is affected by many factors: heat, humidity, type of substrate, texture, inks used, and application technique. Our suggestions and recommendations concerning the use and application of our products are based on tests we believe are reliable. However, the purchaser must test the suitability of our products for his intended use under his own operating conditions. American BiltRite Inc. Assumes no liability for claims beyond the replacement value of any defective products, and is no way for consequential or incidental damages. These products are not suitable for prolonged outdoor exposure.

The values noted in above technical specification are given only for customers' reference and should not be used in writing specifications.



AMERICAN BILTRITE INC.
EXCELLENCE THROUGH QUALITY

Industriezone 23, B-9600 Ronse, Belgium
tel: +32 (0)55/23.51.51 fax: +32 (0)55/23.51.61
e-mail: info@idealabi.com website: www.idealabi.com

