


All the ESD Garments appears in this catalogue are IEC 61340-5-1 and ANSI.ESD 20.20 Standards.

Washing Instructions recommended for all fabric types are as shown at these symbols (max temp. recommended is 60 degrees)



ESD Smock UX Design

Provided as (see next pages):

Comfortable and breathable Static dissipative smock, For use in EPA - Electrostatic Protective Area
Unisex Design 3/4 length

Easy snap fastening, hidden Nickel free snaps
One breast pocket with ESD logo, Two hip pockets

Optional:

- V-neck design
- Full Length
- Internal Breast pocket
- EPA Symbol on sleeve
- Pen/badge holder strip
- Any other change by demand
- Additional Conductive cuffs



UX01/ UX01 DCE/ UX01 NS – UX Smocks made of SF01 fabric

UX30/ UX30 DCE/ UX30 NS – UX Smocks made of SF30 fabric

UX40/ UX40 DCE/ UX40 NS – UX Smocks made of SF40 fabric

UX50 – UX Smock made of SF50 fabric

Size charts

| Size | Chest | Length | Sleeve | Shoulders |
|------|-------|--------|--------|-----------|
| XS | 55cm | 85cm | 52.5cm | 45cm |
| S | 59cm | 89cm | 55.5cm | 47cm |
| M | 63cm | 93cm | 58.5cm | 49cm |
| L | 67cm | 97cm | 61.5cm | 51cm |
| XL | 71cm | 101cm | 64.5cm | 54cm |
| XXL | 75cm | 105cm | 67.5cm | 57cm |
| 3XL | 79cm | 109cm | 70.5cm | 60cm |
| 4XL | 83cm | 113cm | 73.5cm | 63cm |
| 5XL | 87cm | 117cm | 76.5cm | 66cm |