# **Soldering Tools and Equipment**

Product Catalog 2010



Soldering/Desoldering

**Convection Rework** 

Fume Extraction

Fluid Dispensing





www.beasuperproducer.com

### **PCT-1000 Programmable Pre-heater**



#### **Key Features & Benefits**

Adds heat capacity and enables lower process temperatures

- Used in a variety of processes including soldering, desoldering, SMD rework
- Provides faster production rates while lowering overall process temperatures.
- 2 modes: manual for constant heater temperature and profile for greater control
- 4 programmable heating zones and 1 cooling zone
  Storage for up to 50 user defined profiles for easy set-up
- Heater control with temperature controlled either at the heater output or at the board
  High efficiency vortex heater design maximizes
- ramp to temperature for increased productivity

See Board Holders options on pages 24 and 26

The PCT-1000 is a fully Programmable Pre-heater offering more heat, lower temperatures for faster and higher quality results.

The PCT-1000 provides users exceptional ability to increase heat capacity with highly controlled thermal output.

The PCT-1000 can be used as a stand alone unit or as part of the MRS-1000 Modular Rework System.

| Part No.     |   | Description            |
|--------------|---|------------------------|
| PCT-1000     | 1 | Programmable Preheater |
| Includes:    |   |                        |
| PCT-FS1      | 2 | PCT-1000 Foot Switch   |
| AC-TCK-24-36 | 3 | Thermocouple           |
|              | • |                        |



#### **Technical Specifications**

| Size                | 330 x 203 x 76mm<br>(13" x 8" x 3") |  |  |
|---------------------|-------------------------------------|--|--|
| Weight              | 3.4kg (7.5 lbs)                     |  |  |
| Rated Power         | 1200 W                              |  |  |
| Input Voltage       | 100-240 VAC, 50/60 Hz               |  |  |
| Storage Temperature | 0°C to 50°C                         |  |  |
|                     | (32°F to 122°F)                     |  |  |
| Air Flow            | 19 cfm                              |  |  |
| Temperature Range   | Up to 350°C (622°F)                 |  |  |
| Operational Modes   | Setup, Run, Manual,                 |  |  |
|                     | Active Setup                        |  |  |
| Display             | LCD 20 x 4 display                  |  |  |
|                     | segments                            |  |  |
| Number of Programs  | 50 memory locations                 |  |  |
| Number of Zones     | 5 (4 Heat Zones, 1 Cool             |  |  |
|                     | Down Zone)                          |  |  |



The ATH-1000 and LM-1000 are both attached to the back of the PCT-1000 when the components are used together, as part of the MRS System.

## LM-1000 Light Magnifier



### **Key Features & Benefits**

- Integrated light and magnifier
- 4x magnification lens
- Integrated LED lighting system for shadow free illumination
- Can be used with the MRS System or as standalone operation

| Part No. | Description                          |   |
|----------|--------------------------------------|---|
| LM-1000  | Light Magnifier (without base plate) | * |
| LM-BP    | Base Plate for Light Magnifier       |   |
|          |                                      |   |

\* As part of the MRS-1000, the LM-1000 is attached to the back of the PCT-1000, see page 23. The LM-BP can be ordered separately when the LM-1000 is used as a stand-alone unit.


24

### **Technical Specifications**

| Weight        | 2.9kg (6.5 lbs) |
|---------------|-----------------|
| Magnification | 4x              |
| Lighting      | 8 LEDs, white   |
| Power         | 24V DC          |

www.beasuperproducer.com - www.okinternational.com

### **Board Holders for PCT-1000 & PCT-100 Pre-heaters**





BH-1000 Post-Rail Board Holder. Includes: 4 posts, 2 rails with sliding clips, 4 support pins and flat-head support



BH-PK1000 Board Holder Pin Kit. Includes: 2 discs,2 long pins, 2 short pins