
Omniflex & BVX Arms











The **Omniflex Arms** (Ø63mm) are designed for higher airflow rates and effective fume capture from greater distances. A unique ball/socket design provides an unmatched flexibility in manoeuvring and positioning. The arms can be adjusted in working length or radius, simply by adding or removing Omniflex components. ESD conformance is ensured through the use of fully conductive material.

Key Features & Benefits

- ▶ 140m³/h (85cfm) air flow rating (varies with nozzle)
- 63mm (2.5") diameter
- 0.6m (24") long with optional extensions of 300mm (12")

Omniflex Arms are compatible with BVX-200* and MFX units

Part No.		Description
EA1122	2	Omniflex Arm ESD with Rectangular Nozzle
EA1124	3	Omniflex Arm ESD with Tapered Nozzle
EA1126	1	Omniflex Arm ESD with Large Hood 350 x 212mm (14" x 8.5")
Q-AD426530		Replacement nozzle - Rectangular
Q-AD426550		Replacement nozzle - Tapered
Q-AD426560		Replacement nozzle - Large Hood
AC1101	4	Damper for Omniflex Arm
AC1102		Omniflex Arm Extension 30cm (12")
*R\/X_200 series	is o	nly rated for one EA1122 arm one EA1126 arm or two EA1124 arms

3VX-200 series is only rated for one EA1122 arm, one EA1126 arm or two EA1124 arms.

The **BVX Arms** (Ø50mm) are most economic solution while providing good airflow rates and high flexibility. The spiral rolled duct can be tightened in stiffness and can be positioned precisely. The BVX Arm-K2 kit includes a mounting plate and c-clamps for universal mounting. A Y-connection piece is available to connect two BVX Arms to one hose.

Key Features & Benefits

- ▶ 75m³/h (45cfm) air flow rating
- ▶ 50mm (2") ducting with 40mm (1.75") nozzle
- 710mm (28") long

BVX Arms compatible with all units

Part No.		Description
BVX-ARM-K1	5	1 BVX-ARM 760mm (30") long with 1.8m (6') long hose and
		table bracket with C-clamps
BVX-ARM-K2		1 BVX-ARM 760mm (30") long and table bracket with C-clamps
BVX-ARM		Arm flexible ESD safe, 760mm (30") long
BVX-ARML		Arm flexible ESD safe, 1.5m (59") long with arm clip

Connection Hoses for Omniflex and BVX Arms

6	Connection Hose 2.5m xØ63mm (8" x 2.5") with clamps	
6	Connection Hose 3.5m xØ63mm (12" x 2.5") with clamps	
6	Connection Hose 7.5m xØ63mm (25" x 2.5") with clamps	/
7	Y-Piece for Ø63mm (2.5") hose with clamps	
	6 6	 6 Connection Hose 2.5m xØ63mm (8" x 2.5") with clamps 6 Connection Hose 3.5m xØ63mm (12" x 2.5") with clamps 6 Connection Hose 7.5m xØ63mm (25" x 2.5") with clamps 7 Y-Piece for Ø63mm (2.5") hose with clamps

34